

KillTest

高品質 より良いサービス



練習問題

<https://www.killtest.jp>

1年間無料アップデート

Exam : 300-710

Title : Securing Networks with
Cisco Firepower (SNCF)

Version : DEMO

1.What is a result of enabling Cisco FTD clustering?

- A. For the dynamic routing feature, if the master unit fails, the newly elected master unit maintains all existing connections.
- B. Integrated Routing and Bridging is supported on the master unit.
- C. Site-to-site VPN functionality is limited to the master unit, and all VPN connections are dropped if the master unit fails.
- D. All Firepower appliances can support Cisco FTD clustering.

Answer: C

2.Which two conditions are necessary for high availability to function between two Cisco FTD devices? (Choose two.)

- A. The units must be the same version
- B. Both devices can be part of a different group that must be in the same domain when configured within the FMC.
- C. The units must be different models if they are part of the same series.
- D. The units must be configured only for firewall routed mode.
- E. The units must be the same model.

Answer: A, E

3.On the advanced tab under inline set properties, which allows interfaces to emulate a passive interface?

- A. transparent inline mode
- B. TAP mode
- C. strict TCP enforcement
- D. propagate link state

Answer: D

4.What are the minimum requirements to deploy a managed device inline?

- A. inline interfaces, security zones, MTU, and mode
- B. passive interface, MTU, and mode
- C. inline interfaces, MTU, and mode
- D. passive interface, security zone, MTU, and mode

Answer: C

5.What is the difference between inline and inline tap on Cisco Firepower?

- A. Inline tap mode can send a copy of the traffic to another device.
- B. Inline tap mode does full packet capture.
- C. Inline mode cannot do SSL decryption.
- D. Inline mode can drop malicious traffic.

Answer: A