

# *KillTest*

更に上のクオリティ 更に上のサービス



## 問題集

<http://www.killtest.jp>

1年で無料進級することに提供する

**Exam** : **642-737**

**Title** : Implementing Advanced  
Cisco Unified Wireless

**Version** : DEMO

1.Which two considerations must a network engineer have when planning for voice over wireless roaming?  
(Choose two.)

- A. Roaming with only 802.1x authentication requires full reauthentication.
- B. Full reauthentication introduces gaps in a voice conversation.
- C. Roaming occurs when e phone has seen at least four APs.
- D. Roaming occurs when the phone has reached -80 dBs or below.

**Answer:** A,B

2.Which three of the items listed are required configuration parameters for the WLC to enable NAC out-of-band single sign-on when implementing NAC appliances? (Choose three.)

- A. EAP authentication
- B. web authentication
- C. SNMP
- D. RADIUS accounting
- E. WLAN > SNMP NAC enabled
- F. WLAN > RADIUS NAC enabled

**Answer:** C,D,E

3.An engineer is responding to a man-in-the-middle attack and needs to enable security features to prevent such attacks in the future. What security feature would prevent a manin-the-middle attack?

- A. Management Frame Protection
- B. ACL
- C. Enable client and infrastructure MFP
- D. AAA Override

**Answer:** C

4.Refer to the exhibit.

The screenshot shows the 'WLANs > Edit' configuration page in the Cisco WLC v7.0 GUI, with the 'Security' tab selected. The 'Client Exclusion' feature is enabled with a 'Timeout Value (secs)' of 0. Other security features like 'Management Frame Protection (MFP)' and 'DTIM Period' are also visible.

Feature	Configuration
Allow AAA Override	<input type="checkbox"/> Enabled
Coverage Hole Detection	<input checked="" type="checkbox"/> Enabled
Enable Session Timeout	<input checked="" type="checkbox"/> 1800 Session Timeout (secs)
Aironet IE	<input checked="" type="checkbox"/> Enabled
Diagnostic Channel	<input type="checkbox"/> Enabled
IPv6 Enable	<input type="checkbox"/>
Override Interface ACL	None
P2P Blocking Action	Disabled
Client Exclusion	<input checked="" type="checkbox"/> Enabled Timeout Value (secs): 0
<b>HREAP</b>	
H-REAP Local Switching	<input type="checkbox"/> Enabled
Learn Client IP Address	<input checked="" type="checkbox"/> Enabled
<b>DHCP</b>	
DHCP Server	<input type="checkbox"/> Override
DHCP Addr. Assignment	<input type="checkbox"/> Required
<b>Management Frame Protection (MFP)</b>	
Infrastructure MFP Protection	<input checked="" type="checkbox"/> (Global MFP Disabled)
MFP Client Protection	Optional
<b>DTIM Period (in beacon intervals)</b>	
802.11a/n (1 - 255)	1
802.11b/g/n (1 - 255)	1
<b>NAC</b>	
State	<input type="checkbox"/> Enabled

What is the effect of setting Client Exclusion to Enabled and set to a Timeout Value of 0 seconds in a Cisco WLC v7.0?

- A. Excluded clients must be manually removed from the excluded list.
- B. Client exclusion will not occur.
- C. Client exclusion timeout will be determined by the IDS module.
- D. Clients will only be disconnected and not excluded.

**Answer: A**

5.What NAC appliance component is configured to create user roles, meet remediation requirements, and handle checking for device compliance?

- A. NGS
- B. NAA
- C. NAS
- D. NAM

**Answer: D**