KillTest

高品質　より良いサービス



練習問題

https://www.killtest.jp

1年間無料アップデート

Exam : **C2090-635**

Title : IBM Cognos 10 BI OLAP Developer

Version : DEMO

1.When the model contains two data sources that provide date values, how can the developer avoid ambiguity when Transformer sets the current time period?
A. Disable the data source's ability to set the current time period.
B. Assign the current date (obtained from the system clock) as the current period.
C. Let Transformer assign the date closest to the model's creation date as the current period.
D. Enter the initial current period and adjust it to match the system date and time.
Answer: A

2.Where can a developer change relationships to create a structure different from what the data suggests.?
A. Categories Diagram
B. Dimension Map
C. Data source property sheet
D. Level property sheet
Answer: A

3.What must be done to make the cube data available in Analysis Studio?
A. Use the PowerCube Connection Utility to publish the cube.
B. Create a data source connection to the cube in Transformer.
C. Publish the PowerCube as a data source and a package.
D. Generate a package that contains a data source connection to the cube.
Answer: C

4.A developer added a manual level in the time dimension. During category generation, the developer gets a warning that Transformer is not able to relate the categories to the parent levels.
What must be done to ensure Transformer relates the categories correctly?
A. Specify a date function for each level.
B. Specify date input format.
C. Specify an Invalid Dates category.
D. Specify a time-state rollup.
Answer: A

5.What can be done if a regular time dimension is added to a model, and the levels Year, Quarter, and Month are not automatically generated?
A. Set the date input format for the time dimension.
B. Set the data class of the source category to Date.
C. Change the numeric time sequence for each level.
D. Create a non-standard time dimension with the new levels.
Answer: B