

# *KillTest*

更に上のクオリティ 更に上のサービス



## 問題集

<http://www.killtest.jp>

1年で無料進級することに提供する

**Exam** : **HH0-380**

**Title** : Hitachi Data Systems  
Architect - Business  
Continuity

**Version** : DEMO

1.How does a storage administrator obtain the Hitachi Device Manager (HDvM) CLI software?

- A.Install it from the Hitachi Command Suite DVD.
- B.Install the RAID Manager/CCI software.
- C.Download it from the HDvM server.
- D.Download the HDvM CLI license.

**Answer: C**

2.Which two statements regarding the Hitachi Dynamic Link Manager Least I/O and Least Block algorithms are true? (Choose two.)

- A.The Least I/O and Least Block algorithms redirect the I/Os to a single path determined by the algorithms.
- B.The Least I/O and Least Block algorithms redirect the I/Os to a pair of paths determined by the algorithms.
- C.The Extended Least I/O and Extended Least Block algorithms distribute sequential I/Os to a set of paths and random I/Os to another set ofpaths.
- D.The Extended Least I/O and Extended Least Block algorithms distribute I/Os to paths depending on whether the I/O involves sequential orrandom access.

**Answer: A,D**

3.Which two operations would be performed on a VSP using the Element Manager feature of Hitachi Device Manager? (Choose two.)

- A.Change the ports settings of a storage system.
- B.Define tiering policies for Hitachi Tiered Storage Manager.
- C.Access external storage management functions.
- D.Launch the maintenance procedure for Customer Replaceable Parts.

**Answer: A,C**

4.A customer has concerns about high availability and single-point failure for their VSP environment and they are planning to implement a multi-pathing software.Which two Hitachi Dynamic Link Manager (HDLM) features will assist this customer? (Choose two.)

- A.HDLM automatically redirects I/O operations to alternate paths if a failure occurs.
- B.The HDLM server monitors the client hosts' multi-pathing agents and redirects I/Os to an available path if a path failure occurs.
- C.HDLM collects path error information and preventively sets a path offline if the error threshold is exceeded.
- D.When a failed path becomes available,HDLM places the recovered path back online.

**Answer: A,D**

5.Which feature allows the naming of LDEVs using Hitachi Device Manager CLI?

- A.LDEV Naming
- B.LDEV Labeling
- C.LDEV Tagging
- D.LDEV Editing

**Answer: B**

6.You want to monitor the storage capacity used by an application.Which feature of Hitachi Device Manager would you use to achieve this?

- A.device groups
- B.host groups
- C.logical groups
- D.application groups

**Answer: C**

7.On a server with intensive sequential I/O profile, you have set Extended Round Robin within Hitachi Dynamic Link Manager.Which two benefits result from implementing this algorithm? (Choose two.)

- A.tracks preloaded to cache
- B.blocks held permanent in Read Cache
- C.no tracks preloading on the system
- D.efficient cache usage on the storage system

**Answer: A,D**

8.You want to restart the Hitachi Command Suite (HCS) services running on a Windows server.Which tool would you use?

- A.Windows Services panel
- B.HCS GUI
- C.CLI command "hcmdssrv"
- D.Windows Task Manager

**Answer: C**

9.A storage manager needs to add a new server to the Hitachi Device Manager (HDvM) database.As an alternative to running a host scan, which two actions are available to discover and identify the new server? (Choose two.)

- A.Use the Host Data Collector.
- B.Install HDvM Agent on the host.
- C.Execute the AddNewHost CLI command.
- D.Run the Import Hosts utility.

**Answer: A,B**

10.You use Hitachi Device Manager to provision storage.During the provisioning process, what information must you provide? (Choose two.)

- A.the name of the host being provisioned from the storage system
- B.the WWN of the FC port of the storage system connected to the host's HBA
- C.the FC port name of the storage system connected to the host's HBA
- D.the FC path priority settings

**Answer: A,C**