

KillTest

高品質 より良いサービス



練習問題

<https://www.killtest.jp>

1年間無料アップデート

Exam : HPE6-A89

**Title : HPE Networking Comware
Exam**

Version : DEMO

1.Scenario: You are configuring port GigabitEthernet1/0/10 on a Comware switch. The port should belong to VLAN 20 and should not tag traffic.

Which two commands must you use?

- A. port link-type trunk
- B. port link-type access
- C. port default vlan 20
- D. vlan permit 20

Answer: BC

2.Which command enables DNS lookup on a Comware device?

- A. dns resolve enable
- B. ip domain-lookup
- C. enable dns lookup
- D. dns client enable

Answer: B

3.Which type of ACL in Comware matches only on the source IP address?

- A. Advanced ACL
- B. Standard ACL
- C. Layer 3/4 ACL
- D. VLAN ACL

Answer: B

4.Which mode must an interface be in to carry traffic for multiple VLANs?

- A. Trunk
- B. Hybrid
- C. Access
- D. Monitor

Answer: A

5.What is the primary goal of implementing QoS on a network switch?

- A. Improve routing speed
- B. Enhance VLAN segmentation
- C. Prioritize critical traffic over less important traffic
- D. Encrypt sensitive traffic

Answer: C