

KillTest

更に上のクオリティ 更に上のサービス



問題集

<http://www.killtest.jp>

1年で無料進級することに提供する

Exam : **JN0-380**

Title : Wireless LAN, Specialist
(JNCIS-WLAN)

Version : DEMO

1.Which RingMaster license is needed to enable the RingMaster API?

- A.base license
- B.USM license
- C.Agent license
- D.AP license

Answer: C

2.A small business is using Radio Frequency (RF) planning to establish and limit the number of access points (APs) needed for a coverage area.The company is trying to decide what to use for the baseline association rate for clients to connect to the access points.

Which two statements are correct? (Choose two.)

- A.A baseline association rate of 54 Mbps requires more APs than a baseline association rate of 18 Mbps.
- B.A baseline association rate of 18 Mbps requires more APs than a baseline association rate of 54 Mbps.
- C.A baseline association rate of 54 Mbps requires the client to be farther away from the AP to reach the targeted rate.
- D.A baseline association rate of 18 Mbps requires the client to be farther away from the AP to reach the targeted rate.

Answer: A,D

3.You are using the RF Planning tool in RingMaster to configure a data capacity plan for a client.

Which three settings are required on the Data Capacity Options page? (Choose three.)

- A.AP authentication mode
- B.Per Station Throughput
- C.Expected Station Count
- D.Coverage Area
- E.Station Oversubscription Ratio

Answer: B,C,E

4.Multiple users are complaining that their wireless connections are not working.

Which RingMaster screen would the administrator use for troubleshooting?

- A.Alarms
- B.Clients
- C.Monitor
- D.Verification

Answer: C

5.A network administrator must perform a software upgrade of a factory-default wireless LAN controller (WLC) using the CLI.

Which three actions are required? (Choose three.)

- A.Set the inactive boot partition to the active boot partition.
- B.Add an upgraded license for the new image.
- C.Copy the new image to the inactive boot partition using TFTP.
- D.Reboot the controller.
- E.Upgrade the connected access points (APs) before upgrading the controller.

Answer: A,C,D

6.As a designer, you know that RingMaster needs only the principle radio frequency (RF) obstacles for planning.

Which three obstacles should be included? (Choose three.)

- A.external walls
- B.ceilings
- C.partitions
- D.file cabinets
- E.windows

Answer: A,C,E

7.Which UDP port is used for RADIUS authentication by default?

- A.1813
- B.5001
- C.1812
- D.8080

Answer: C

8.Your manager asks you to verify that all access points in a cluster have a primary and secondary controller assigned.

Which CLI command should you use to verify this?

- A.show cluster
- B.show ap status
- C.show mobility-domain
- D.show cluster ap

Answer: D

9.You want to copy 802.11 protocol messages from the RF channel to a specified observer running a protocol analyzer.

Which WLC feature would you use?

- A.IGMP
- B.RF Snoop
- C.trace
- D.RF ping

Answer: B

10.You have wireless clients that are not part of the corporate network, but you want to allow them access to the Internet without requiring a username and password.

Which type of Service Profile in RingMaster should you configure?

- A.Mesh Service
- B.Voice Service
- C.Open Access Service
- D.Secure Service

Answer: C